

Astro

26' Ku UPLINK / HD PRODUCTION HYBRID OVERVIEW

Production

For-A HVS-390 Hanabi Switcher 2 M/Es available, 16 input, 8 output (4) Keyers per ME, (4) DVEs, (4) Chroma Keyers, Still Store

Records

(2) AJA KiPro HDD Recorder (1) AJA HELO H.264 Recorder Wired for up to 6 Recorders

Camera Equipment

Multichannel Mux Available

Wired for up to 4 CCUs Camera configs built to event spec

Transmission

2.4m AVL Ku Uplink Antenna with 4-Port Feed(2) 125-watt Ku Advantech Amplifiers(2) Adtec EN-100 Encoders(2) Adtec RD60 Decoders

Communications

RTS Cronus 32-Port Digital Matrix (4) RTS PL Channels (4) RTS Telephone Interface (4) Wet IFB Channels

(2) Biscuit Boxes

Terminal Equipment

40x40 BlackMagic Design HD/ASI Router 4x4 Audio Embed/De-Embed (2) Configurable Integrated Multiviewer Outputs (3) HD Frame Syncs Frame syncs on all switcher inputs

Graphics Facilities

(1) Mac Mini with Playback Pro Software Wired for 1 Dual-Channel Graphics System

Cable Inventory

(1) 500' TAC-8 Fiber Mult

Audio Facilities

Yamaha TF1 Digital Mixing Console 16 Fader / 32 DSP Inputs 32x16 Analog, 64x64 MADI 16x8 Remote Stagebox

Support

(2) Fostex Speakers

(3) Throwdown HD Monitors

(2) SDI-HDMI Converters

(2) Fiber Rattler Sets

(2) Decimator MD-Cross Converters

Power Requirements

1 Phase, 80 Amps, 208 Volts 2 Hot Legs, 1 Neutral, 1 Ground 100' feeder cable with camlock connectors 10kW Generator On Board

Connectivity

(2) VoIP Phone Lines

(2) Verizon Cellular POTS Lines

Truck Dimensions

GVW – 20,000 Lbs Dimensions – 29ft L, 9ft W, 13.5ft H working footprint

Resolutions & Frame Rates

1080i, 720p 59.94

For mobile unit inquiries, call us at 615-431-1400 or e-mail contact@tndv.com
Mobile unit equipment complement is subject to change without notice. Additional equipment is available as needed.